

Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



Motor type : 1AV3104D

INNOMOTICS GP - 100 L - IM B5 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data **Safe Area**

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{(3)}$			$\cos\phi^{(3)}$			I_A/I_N	M_A/M_N	M_R/M_N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																	
220	Δ	50	0.75	-/-	3.90	710	10.1	75.0	75.7	73.1	0.67	0.58	0.45	3.7	1.5	2.1	IE3
380	Y	50	0.75	-/-	2.25	710	10.1	75.0	75.7	73.1	0.67	0.58	0.45	3.7	1.5	2.1	IE3
IM B5 / IM 3001			FS 100 L			IP55	UKCA	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 46.80 s | 59.70 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	61.0 / 69.0 dB(A) ²⁾	64.0 / 72.0 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0096 kg m ²		Thermal class	F
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	20 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled
			Carbon footprint (without options)	107kg

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm ²
Material of terminal box	Aluminium	Main cable entry	2xM32x1.5
Type of terminal box	TB1 F00	Main cable gland	2 plugs
Contact screw thread	6xM4		

I_A/I_N = locked rotor current / current nominal
 M_R/M_N = locked rotor torque / torque nominal
 M_R/M_N = break down torque / nominal torque

¹⁾ L_{10mh} according to DIN ISO 281 10/2010
²⁾ at rated power / at full load

³⁾ Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by IPC	Approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	
INNOMOTICS	Document type Technical data sheet	Document status Released		Document number TDS-250915-134009	
	Document title 1LE1003-1AD42-1FA4	Revision AA	Creation date 2025-09-15	Language en	Page 1/1
Restricted © Innomotics 2025					