

# Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



**Motor type : 1AV3164D**

**INNOMOTICS GP - 160 L - IM B3 - 8p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

**Electrical data** **Safe Area**

U [V]	$\Delta/Y$	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{(3)}$			$\cos\phi^{(3)}$			$I_A/I_N$	$M_A/M_N$	$M_R/M_N$	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	$I_V/I_N$	$T_A/T_N$	$T_R/T_N$	
<b>DOL duty (S1) - 155(F) to 130(B)</b>																	
400	$\Delta$	50	7.50	-/-	17.00	730	98.0	87.3	87.9	86.9	0.73	0.64	0.52	5.8	2.3	2.7	IE3
690	Y	50	7.50	-/-	9.80	730	98.0	87.3	87.9	86.9	0.73	0.64	0.52	5.8	2.3	2.7	IE3

IM B3 / IM 1001	FS 160 L	IP55	UKCA	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
Environmental conditions : -20 °C - +40 °C / 1000 m			Locked rotor time (hot / cold) : 24.60 s   39.50 s		

**Mechanical data**

Sound level (SPL / SWL) at 50Hz 60Hz	70.0 / 78.0 dB(A) <sup>2)</sup>	66.0 / 79.0 dB(A) <sup>2) 3)</sup>	Vibration severity grade	A
Moment of inertia	0.1300 kg m <sup>2</sup>		Thermal class	F
Bearing DE   NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
<b>Bearing lifetime</b>			Direction of rotation	bidirectional
$L_{10mh}$ $F_{Rad min}$ for coupling operation 50 60Hz <sup>1)</sup>	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	110 kg
Grease nipple	-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled
			Carbon footprint (without options)	485kg

**Terminal box**

Terminal box position	top	Max. cross-sectional area	16.0 mm <sup>2</sup>
Material of terminal box	Aluminium	Main cable entry	2xM40x1.5
Type of terminal box	TB1 J00	Main cable gland	2 plugs
Contact screw thread	6xM5		

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_R/M_N$  = break down torque / nominal torque  
<sup>1)</sup>  $L_{10mh}$  according to DIN ISO 281 10/2010  
<sup>2)</sup> at rated power / at full load  
<sup>3)</sup> Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LV	Technical reference	Created by IPC	Approved by	<b>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</b>	
<b>INNOMOTICS</b>	Document type Technical data sheet	Document status Released			
	Document title <b>1LE1003-1DD43-4AA4</b>	Document number TDS-251208-145749			
Restricted © Innomotics 2025		Revision AA	Creation date 2025-12-08	Language en	Page 1/1